



Product Code	OHS-CHR-1705
Description	Medley Dualflow Overhead Shower 120mm Round Shape with Silk & Rain
Flow Rate	Silk - 12.59 LPM @ 3 bar Rain - 13.36 LPM @ 3 bar
Flow regulator	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM & GB-8.0 LPM @ 4.0 Bar pressure) one can regulate the flow rate.
Operating pressure	1 - 5 bar
Recommended Water Pressure	3.0 Bar
Mount Type	Wall Mounting
Spray Modes	Silk (patented) and Rain functions
Material Composition Specification in Percentage	<p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>ABS Specification Specific Gravity g/cm² (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)</p>
Technology	<p>Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.</p> <p>Push-Button System - Effortlessly switch between Rain and Silk spray modes for a personalized shower experience.</p>
Finish	Salt Spray (350 hrs + Validated) Adhesion (Pass)
Available Finishing	Black Chrome (BCH), Black Matt (BLM), Blush Gold Bright PVD (BGP) & Gold Bright PVD (GBP)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.