





| Product Code                      | LAG-CHR-91227K   |
|-----------------------------------|--|
| Description                       | Exposed Part Kit of Single Lever In-wall Manual Valve, 35 mm Cartridge (Compatible with    |
|                                   | ALD-227 & ALD-229)   |
| Recommended Water Pressure        | 0.5 Bar - 5 Bar  |
|                                   | Brass Rod as per IS:319-1989   |
|                                   | Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)      |
| Brass Specification in Percentage |  |
|                                   | Brass Sheets as per IS:410-1977  |
|                                   | Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)     |
|                                   | Plating: Nickel-10.0 micron Chromium-0.3 micron  |
| Finish                            | Salt Spray (500 hrs + Validated)   |
|                                   | Adhesion (Pass)  |
| Available Single Colour Finishing | Black Chrome (BCH), Black Matt (BLM), Gold Matt-PVD (GMP), Gold Bright-PVD (GBP) &         |
|                                   | Blush Gold Bright PVD (BGP)  |
| Available Dual Colour Finishing   | <br>  Black Matt & Black Chrome (BBC), Gold Matt-PVD & Gold Bright-PVD (GMG), Black Matt & |
| (First Colour for Body & Second   | Gold Matt-PVD (BGM)  |
| for Lever)                        | Gold Matt-PVD (BGM)  |

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.