





Product Code	OHS-CHR-1675WL
Description	Duoflo Shower Round Shape 450mm AISI 304 stainless steel without Chromo therapy light with Installation kit for false ceiling • 2-functions ▪ Rain, ▪ 4 X Mist
Flow Rate	Rain - 67.15 LPM @ 3 bar Mist - 1.99 LPM @ 3 bar
Flow regulator	By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	1.0 Bar - 3.0 Bar
Mount Type	Ceiling Mounting
Spray Modes	Rain & Mist Functions
Material Composition Specification in Percentage	STAINLESS STEEL: Nickel 8.0-11.0, Chromium 18.0-20.0, Manganese 0.0 - 2.0, Carbon 0.0-0.08, Iron Remainder (AISI 304) ABS: Specific Gravity (g/cm²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26, Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (OC) 78-102
Technology	Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.
Finish	Salt Spray (350 hrs + Validated) Adhesion (Pass)
Available Finishing	Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Blush Gold Bright PVD (BGP), Black Matt (BLM), Gold Bright PVD (GBP), Gold Matt PVD (GMP) & Graphite (GRF)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	